EN **Instruction manual**



Refrigerator freezer

We thank you for the confidence you have shown by purchasing our appliance.
We wish you find a lot of pleasure in its use.

The appliance is intended to be used in household and similar applications such as
- *staff kitchen areas in shops, offi ces and other working environments;*
- *bed and breakfast type environments.*

***It is NOT intended** to be used in:*
- *farm houses and by clients in hotels, motels and other residential type environments;*
- *catering and similar non-retail applications.*

***Refrigerator freezer** (hereinafter: the appliance) consists of two parts: the upper part is the refrigerator and the lower part is the freezer.*
***The refrigerator** is intended for storing fresh food at temperatures above 0°C.*
***The freezer** is intended for freezing fresh food and for long-term storage of frozen food (up to one year, depending on the type of food).*

Important notes and warnings 3
Advice for saving power with refrigeration appliances 5
Appliance description 6
Installation and connection 8
Changing the direction of door opening 10
Operating the appliance with mechanic controls... 13
Appliance with electronic control 14
Appliance interior equipment 23
Recommended distribution of food in the appliance 27
Storing food in the refrigerator 28
Storing food in the FreshZone drawer 29
Storing food in the ZeroZone drawer 30
Freezing and storing frozen food 31
Defrosting the appliance 34
Cleaning the appliance 35
Troubleshooting 36
Information about appliance noise 38

Important notes and warnings

- The appliance is manufactured in compliance with the effective safety standards. However, it can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved.
- Before connecting the appliance to the power mains, please read carefully the instructions for use which describe the appliance and its correct and safe use. The instructions apply for several appliance types/models; thus, settings or equipment may be described herein which is not available in your appliance. The instruction manual includes the NO FROST version/model of the freezer which is fitted with a fan and in which the defrosting process is automatic.
- Remove the packaging intended for protecting the appliance or particular parts during transport.
- Spacers are fitted on the corners of the doors. Remove them and insert the supplied plugs into their slots (only in some models).
- Before connecting the appliance to the power mains, let the appliance rest in a vertical position for approximately 2 hours. This will reduce the possibility of operation faults due to the effect of transport on the cooling system.
- The appliance must be connected to the power mains and grounded in compliance with the effective standards and regulations.
- The appliance may not be used outdoors and it may not be exposed to rain.
- Before cleaning the appliance, unplug the appliance from the power mains (unplug the power cord from the wall outlet).
- If the power cord is damaged, it must be replaced by a service technician or other adequately trained person.
- If the appliance will be out of use for a prolonged period of time, switch it off using the relevant button, and unplug the appliance from the power

mains. Empty the appliance, defrost it, clean it, and leave the door ajar.

- To protect the environment, take the obsolete appliance to an authorized home appliance collection center.
- Packaging is made of environmentally friendly materials that can be recycled, disposed of, or destroyed without any hazard to the environment.
- Do not let the children play with the appliance.
- Cleaning and user maintenance shall not be made by children without supervision.
- Rating plate can be found in the appliance interior. If the language on the rating plate is not the language of your choice or the language of your country, replace it with the one supplied.
- **WARNING!** Ventilation openings on the appliance or built-in cupboard must be kept clean and unobstructed at all times.
- **WARNING!** Do not use any mechanical accessories or other methods to defrost the appliance, except for those expressly recommended by the manufacturer.
- **WARNING!** During installation, cleaning, and removal of appliance, be careful not to damage the insulation of the parts of the cooling system. This will also prevent pollution.
- **WARNING!** Do not use any electric devices inside the appliance, except for those allowed by the manufacturer of this refrigeration appliance.

The symbol on the product or its packaging indicates that the product should not be treated as normal household waste. The product should be taken to an authorized collection center for waste electric and electronic equipment processing. Correct disposal of the product will help prevent any negative effects on the environment and health of people which could occur in case of incorrect product removal. For detailed information on removal and processing of the product, please contact the relevant municipal body in charge of waste management, your waste disposal service, or the store where you bought the product.

Advice for saving power with refrigeration appliances

- Install the appliance as specified in the instruction manual.
- Do not open the door more often than necessary.
- Occasionally make sure air circulation underneath the appliance is unobstructed.
- Condenser unit on the rear wall should be kept clean (see chapter Cleaning the appliance).
- If the gasket is damaged or does not provide a perfect seal for other reasons, have it replaced as soon as possible.
- Store the food in tightly sealed containers or appropriate packaging.
- Before placing the food in the appliance, cool it to room temperature.
- Defrost frozen food in the refrigerator compartment.
- Remove the drawers from the freezer compartment as described in the instruction manual, in order to make use of the entire interior.
- Defrost your conventional freezer when an approximately 3-5 milimeter layer of of frost or ice has built up on the refrigerated surfaces.
- Make sure the layout of shelves in the compartment is uniform and that the food is placed so that the air can freely circulate in the appliance interior (observe the recommended placement of food as described in the instructions).
- In appliances with a fan, do not block the fan slots.

Appliance description

Conventional appliance



A Refrigerator

1 Control unit
2 Led lighting of refrigerator interior
3 Fan with air ionizer (+ on/off switch)*
4 Bottle rack*
5 Pull-out glass shelf (height adjustable)
6 FreshZone/ZeroZone drawer*
7 CrispZone fruit and vegetables drawer with humidity control
8 Multibox storage bin*
9 SimpleSlide height-adjustable door bin
10 Bottle bin

B Freezer compartment

11 Freezer drawers
12 Glass shelves

13 Caster*
14 Foot*

- Appliance interior equipment may change according to the appliance model.
- The drawers are protected against pulling out. To remove a drawer from the appliance, open it, then lift the front part and pull it out.
- Some models also feature a control unit on the door.

* Only in some models

NoFrost appliance



A Refrigerator

1 Control unit
2 Led lighting of refrigerator interior
3 IonAir air ionizer (+ on/off switch)
4 Bottle rack*
5 Pull-out glass shelf (height adjustable)
6 Refrigerator compartment temperature control*
7 FreshZone/ZeroZone drawer*
8 CrispZone fruit and vegetables drawer with humidity control
9 Multibox storage bin*
10 SimpleSlide height-adjustable door bin
11 Bottle bin

B Freezer

12 Freezer drawers
13 Glass shelves

14 Caster*
15 Foot*

- Appliance interior equipment may change according to the appliance model.
- The drawers are protected against pulling out. To remove a drawer from the appliance, open it, then lift the front part and pull it out.
- Some models also feature a control unit on the door.

* Only in some models

Installation and connection

Selecting the room

- Install the appliance in a dry and well ventilated room. The appliance will operate correctly if the environment temperature is in the interval specified in the table. The appliance class is indicated on the rating plate / label with the basic information on the appliance.

Class	Temperature
SN (subnormal)	from +10°C to +32°C
N (normal)	from +16°C to +32°C
ST (subtropical)	from +16°C to +38°C
T (tropical)	from +16°C to +43°C

Warning: Make sure the room where the appliance is installed is large enough. There should be at least 1 m^3 of space per 8 grams of refrigerant. Amount of refrigerant is stated on the rating plate in the appliance interior.

Installing the appliance

Appliance installation should be carried out by at least two persons to avoid any physical injury or damage to the appliance.

- The appliance must stand level and stable on a solid base. At the front, the appliance is fitted with two adjustable legs that can be used to level the appliance. At the rear side, casters allow for easier installation of the appliance (only with some models).
- There should be a clearance of at least 5 cm between the appliance and any cupboard installed above it, in order to allow adequate cooling of the condenser unit.

- The appliance is supplied with two spacers which should be installed on the lower part of the housing to prevent from pushing the appliance too close to the wall. Appliance may also be installed without the spacers; however, this may increase power consumption.
- Do not expose the appliance to direct sunlight and do not place it near any source of heat. If this cannot be avoided, install an insulation panel.

- The appliance may stand alone or it may be placed ext to a cupboard or a wall. Consider the clearance required to fully open the door in order to allow pulling out the drawers and shelves (see installation diagram).



Connecting the appliance

- Connect the appliance to the power mains using a connection cable. The wall outlet should be fitted with a ground contact (safety socket). Nominal voltage and frequency are indicated on the rating plate/label with basic information on the appliance.
- The appliance must be connected to the power mains and grounded in compliance with the effective standards and regulations. The appliance will withstand short-term deviations from the nominal voltage, but not more than +/- 6%.

Changing the direction of door opening

Version I – controls in the appliance interior

Tools required: socket wrench No. 8, Phillips screwdriver, torx 25, flat screwdriver
The procedure to change the direction of door opening should be carried out by at least two persons.

1. Remove the upper hinge cover (A).
2. Unscrew the upper hinge (B) and remove the upper door (C).
3. Then remove the covering plugs (D), unscrew the mid hinge (E) and remove the lower door (F) from the lower hinge (G).
4. Tilt the appliance backwards (make sure you do not press against the condenser unit on the rear wall of the appliance as this may damage the cooling system), unscrew the lower hinge (G) and the foot (H) and move them to the opposite side. Make sure the washer is installed like it was before disassembly.
5. Move the door hinges (I) to the opposite side.
6. Place the Mid hinge (E) on the lower door (F) and place the lower door on the lower hinge (G). Fasten the mid hinge (the door should be open while you do this). Do not forget to place the washers (J) and covering plugs (M) as they were placed before the disassembly.
7. Place the upper door (C) over the middle hinge (E), remove the covering cap (K) and fasten the upper hinge (B).
8. Install the upper hinge cover (A) and the covering cap (K).
9. Changing the side of the handle (L): remove the covering plugs/caps, undo the screws and fasten the handle on the opposite side. Place the covering plugs/caps on the opposite side.


K
A
B
I
C
E
J
M
I
D
E
L
F
G
H
I
G
H

Version II – Controls on the door

Tools required: socket wrench No. 8, Phillips screwdriver, torx 25, flat screwdriver
The procedure to change the direction of door opening should be carried out by at least two persons.

1. Remove the upper hinge cover (A) and the cover from the connector (B1).
2. Unplug the connector (C), unscrew the upper hinge (D) and remove the upper door (E).
3. Remove the side panels (F) and (G), then unscrew and remove the middle panel (H).
4. Move the upper hinge (A) and the connector and cable to the opposite side. Replace all three panels (F), (G), and (H). Make sure the cable runs through the grooves in the panels like it did before disassembly.
5. Then remove the covering plugs (I), unscrew the mid hinge (J) and remove the lower door (K) from the lower hinge (L).
6. Tilt the appliance backwards, undo the lower hinge (L) and the foot (M) and install them on the opposite side. Make sure the washer is installed like it was before disassembly.
7. Move the door hinges (N) to the opposite side.
8. Place the Mid hinge (J) on the lower door (K) and place the lower door on the lower hinge (L). Fasten the mid hinge (the door should be open while you do this). Do not forget to place the washers (O) and covering plugs (I) as they were placed before the disassembly.
9. Place the upper door (E) on the middle hinge (J). Remove the covering plugs (P) and (B2). Reconnect the connector (C) **and fasten the upper hinge.**
10. Install the over of the upper hinge (A), connector cap (B1), and covering caps (P) and (B2).
11. Changing the side of the handle (R): remove the plugs/caps, undo the screws and fasten the handle on the opposite side. Place the plugs/caps on the opposite side.



Operating the appliance with mechanic controls

CONTROL UNIT 1



A Temperature setting and on/off knob
B Lighting on/off key

Switching the appliance on/off



To switch on: rotate the **A** dial clockwise.

Switching off: Rotate the **A** knob back to the position in which the arrow is aligned with the symbol ⏻ (caution: appliance will remain powered, i.e. there will still be electric current in the appliance).

Adjusting the temperature



- To set the desired temperature, rotate the **A** dial in clockwise direction, i.e. to the right.
- A change in the environment temperature will affect the temperature in the appliance. Adjust the setting with the **A** dial accordingly. Positions towards the **thicker part** of the sign mean a lower temperature in the appliance (cooler). Settings towards the **thinner part of the sign** mean a higher temperature (warmer).



- If the temperature of the room where the appliance is installed is below 16°C, we recommend setting the **A** dial temperature to **the thickest part of the sign.**

Appliance with electronic control

CONTROL UNIT 2



A Temperature setting and on/off knob

Switching the appliance on/off



To switch on: rotate the **A** dial clockwise.

TO switch off: rotate the **A** dial so that the arrow is aligned with the ⏻ sign (caution: appliance will remain powered, i.e. there will still be electric current in the appliance).

Adjusting the temperature



- To set the desired temperature, rotate the **A** dial in clockwise direction, i.e. to the right.
- Recommended setting of the **A** knob is on the eco position.
- A change in the environment temperature will affect the temperature in the appliance. Adjust the setting with the **A** dial accordingly. Positions towards the **thicker part** of the sign mean a lower temperature in the appliance (cooler). Settings towards the **thinner part of the sign** mean a higher temperature (warmer).



- If the temperature of the room where the appliance is installed is below 16°C, we recommend setting the **A** dial temperature to the **thickest part of the sign.**

Freezer boost (super freeze) function (only in some models)



- Use this setting after switching on the appliance for the first time, before cleaning, or 24 hours before inserting a large amount of food.

Switching on the freezer boost (super freeze) function:
Rotate the **A** dial to position ✳.

After the end of the freezer boost cycle, rotate the **A** knob back to the desired setting.

If the freezer boost is not deactivated manually, it will be automatically switched off after approximately 2 days. Then the temperature of the freezer compartment returns to the most recently set value (knob position remains at ✳).

Manually adjustable flap (only with some models of NoFrost appliances)



The flap is located in the fruit and vegetable bin. As a factory setting, it is in position 2.
If it is not possible to reach the right temperature by adjusting the settings with the knob **A**, then set the flap as described in the section »Troubleshooting«.

Operating the conventional appliance



Operating the NoFrost appliance



A On/off switch
B Temperature adjustment and freezer boost key
C1 Refrigerator compartment temperature display
C2 Freezer compartment temperature display
D Freezer boost function display

Switching the appliance on/off

The appliance can be switched on and off with the on/off key **A**.



Adjusting the temperature

- Adjust the temperature as desired with the **B** key.
- Press the **B** key until the desired temperature is set.





Conventional appliance – displays the set temperature of the refrigerator compartment

- Recommended setting is 5 °C.
- If the temperature of the room where the appliance is installed is below 16°C, we recommend setting the temperature to 5 °C or lower.



NoFrost appliance – displays the set temperature of the freezer compartment

- Recommended setting is -18 °C.
- If the temperature of the room where the appliance is installed is below 16°C, we recommend setting the temperature to -18 °C or lower.

Freezer boost (super freeze) function

To activate the freezer boost function, press the **B** key until the symbol **D** lights up.

- Use this setting after switching on the appliance for the first time, before cleaning, or 24 hours before inserting a large amount of food.
  If the function is not deactivated manually, it will be deactivated automatically after approximately two days.

Refrigerator compartment temperature control (only with some models of NoFrost appliances)



- Use the control to regulate the inflow of cool air from the freezer compartment and reach the desired temperature in the refrigerator compartment.
- Set the desired temperature using the button located in the refrigerator compartment. A change in the environment temperature will affect the temperature in the appliance. Adjust the temperature setting accordingly. Positions towards the thicker part of the sign mean a lower temperature in the appliance (cooler). Settings towards the thinner part of the sign mean a higher temperature (warmer).
- If the environment temperature is below 16°C, we recommend a setting towards the thinner part of the sign; if the environment temperature is higher than 32°C, a setting towards the thicker part of the sign is recommended.
- In order to attain the desired temperature in the ZeroZone drawer (only with some models), the thermostat should be set towards the thicker end of the marking.

Caution: Temperature sensor is installed behind the slots found under the dial. For correct operation of the appliance, this area should not be too crowded with food items.

CONTROL UNIT 4

Controls on the door



A Appliance on key and refrigerator compartment off key
B Acoustic alarm off key
C Super cool on/off key
D Refrigerator compartment temperature keys
E Refrigerator temperature display
F Freezer compartment on key and appliance off key
G ECO function on/off key
H Super freeze on/off key
I Freezer compartment temperature keys
J Freezer compartment temperature display

Switching the appliance on/off



Switching the appliance on: Switch on the appliance by briefly pressing the key **A.**

With this model, it is possible to only switch on the freezer compartment while the refrigerator compartment is switched off. This setting can be made in two ways:

- briefly press the **F** key to switch on the freezer compartment only; or
- first briefly press the **A** key to switch on the entire appliance. Then, press and hold (for three seconds) the **A** key to switch off the refrigerator compartment.



When the **A** key is pressed again, the refrigerator compartment will be switched back on.

Switching off the appliance: To switch off the appliance, press and hold (for three seconds) the key **F** (caution: appliance will remain powered, i.e. there will still be electric current in the appliance).

Adjusting the temperature

- To set the temperature in the refrigerator compartment use the keys **D:**
  < lower temperature ; > higher temperature.

- Temperature in the refrigerator compartment can be set from +1°C to +9°C.
- After one of the **D** keys is pressed, the most recent temperature setting will flash on the display **E**. Use the **D** keys to set the desired temperature. Three seconds after the last key was pressed, the most recent temperature setting is stored for the refrigerator compartment.



- To set the temperature in the freezer compartment use the keys I:
  < lower temperature ; > higher temperature.

- Temperature in the freezer compartment can be set from -24°C to -16°C.
- After one of the **I** keys is pressed, the most recent temperature setting will flash on the display **J**. Use the **I** keys to set the desired temperature. Three seconds after the last key was pressed, the most recent temperature setting is stored for the freezer compartment.

Freezer boost function (Super Freeze)



- Use this setting after switching on the appliance for the first time, before cleaning, or 24 hours before inserting a large amount of food.

Switching on the freezer boost (super freeze) function: Press the **H** key. **FF** will appear on the display **J**.

If the freezer boost is not deactivated manually, it will be automatically switched off after approximately 2 days. Then the temperature of the freezer compartment returns to the most recently set value.

Extreme freezing (upper drawer of the freezer compartment)



- In order to quickly freeze fresh food, use the XtremeFreeze function that is only active in the upper drawer of the freezer compartment. It involves intensive blowing of cool air in that part of the appliance. Faster freezing will retain more vitamins, minerals, and nutrients in the food for a longer period of time.

Switching on the freezer boost (XtremeFreeze) function: Press the **H** key an hold it for at least 3 seconds. **EF** will appear on the display **J**.

- With this setting, the compressor will operate continuously and the temperature in the freezer compartment will drop considerably.

- If the setting is not deactivated manually (by pressing the »H« key), it will be deactivated automatically after approximately one day. Freezer compartment temperature will return to the most recent setting.

- Use this setting for freezing smaller amounts of food (up to 2 kilograms) in the upper drawer. When freezing a large amount of food, the setting should be activated 12 hours before the food is placed in the freezer.

Refrigerator boost (Super Cooling) (refrigerator compartment)

- Use this setting after switching on the appliance for the first time, before cleaning, or before inserting a large amount of food.

Switching on the refrigerator boost (super cool) function: Press the **C** key.

If the function is not deactivated manually, it will be deactivated automatically after approximately six hours. Refrigerator compartment temperature will return to the most recent setting.

High temperature alarm



If the temperature inside the appliance is too high, acoustic alarm will be activated (**intermittent tone**) and the **B** key will flash.

- Acknowledge and turn off the acoustic alarm by pressing the **B** key.
- The acoustic alarm will be activated every 24 hours if the temperature in the appliance is not low enough and there is danger of food spoilage. The alarm will be switched off automatically as soon as the temperature in the freezer drops to a level that no longer presents spoilage hazard.
- When the appliance is switched on for the first time, there is a 24-hour delay in temperature alarm operation since the appliance will not have reached the adequate temperature. Thus, unnecessary activation of alarm is prevented.

Open refrigerator door alarm: if the refrigerator or freezer compartment door is open for more than 2 minutes, acoustic alarm will be activated and the **B** key will flash. When the door is closed, the alarm will be deactivated. It can also be switched off by pressing the **B** key.

Eco function



To activate the **Eco** function, press the **G** key. With this function activated, appliance will operate with optimum settings.

Safety block (child safety lock)



Use this function if you do not wish to manually adjust the appliance settings.
To activate, press and hold the **B** key (for three seconds); L will appear on the display **E**.
This will lock all keys except **B**.
To deactivate the safety lock, press the **B** key and hold it for three seconds.

Appliance interior equipment

(* Equipment depends on the model)

Shelf

- For easier access to food and clarity, the shelves can be partly pulled out.
- The shelves may be adjusted tu suit your preferences using the guides in the refrigerator interior. To remove a shelf from the refrigerator, pull it out tot he point when it is stopped by the guide. Then, lift it slightly at the front part and pull it all the way out.
  Store perishables at the back of the shelf where the temperature is the lowest.

*Wire bottle rack**

- Some models also feature a wire bottle holder. The bottle holder is protected against being inadvertently pulled out It can only be pulled out when it is empty. To pull it out, lift is slightly at the back and pull it towards you. Place the bottle holder so that the length of the bottles does not prevent proper closing of the door. The holder can take a maximum load of 9 0.75-liter bottles or 13 kilograms of total weight – see label on the right side in the appliance interior.
- Cans may also be placed on the bottle rack (lengthwise or crosswise).

*Elastic bottle mat**



- Some models feature an elastic mat on which bottles or cans can be placed.
- The mat can also be used as a trivet for hot pans.

CrispZone – fruit and vegetable bin with humidity control

- The bin at the bottom of the refrigerator is intended for storing fruit and vegetables. It provides humidity and prevents the food from drying out.
- Store the food in suitable packaging to prevent them from emitting or taking on odours.
  The bin has integrated humidity regulator which allows setting the humidity according to the amount of food stored.

Smaller amounts of food - push the control slider to the right;
Larger amounts of food - push the control slider to the left;



- Pulling out the bin:
  - Pull out the bin as far as it will go. Then, lift the front part and pull it out completely.

Interior side of the refrigerator door

Mounted on the refrigerator door are compartments (shelves or bins) intended fro storing cheese, butter, eggs, yoghurt and other smaller packages, tubes, cans, etc. There is a bottle shelf at the lower end of the door.

Adjustable door bins



The height of shelves can be adjusted to your preferences without having to take them out of the appliance. Pull the two levers on either side of the shelf towards you and move the shelf down. If you wish to set the shelf higher, you can do so without releasing the two levers.

To remove a bin from the appliance, lift it as far as it will go and pull it out.

*Storage bin (MultiBox)**

- **MultiBox** bin offers a convenient way for storing food with a strong or pungent smell, e.g. ripened or blue-vein cheese, sausages, onions, butter etc.
- The silicone lid provides an air-tight seal that prevents the food from drying out and the odour to spread throughout the refrigerator compartment.
- The silicon lid can also be used as an egg or ice tray.
- If the flexible lid is used as an egg tray, place it directly on the bottom of the door bin and use the open lower part of the Multibox bin to store food in smaller packages – pâté, jams, smaller tubes etc.

Fan*

- The fan placed under the refrigerator compartment ceiling or hidden in the freezer unit will make sure the temperature is distributed more evenly and reduce condensation (dew) on the storage surfaces.

Ionizer (IonAir)*

- **Air ionizer** placed in the refrigerator compartment removes most bacteria, viruses, gases, and unpleasant odours to make sure the air in the refrigerator is always fresh. The food will remain fresh and tasty longer.
- Air ionizer can be switched on and off using the switch located on the fan housing or on the side of the cooling tower (depending on the model).

CONVENTIONAL APPLIANCES

Control unit 1

Switching the fan and ionizer on and off

ON = **OFF =** **0**



When the fan and the ionizer are switched on, a red dot will be visible on the switch.

Control unit 3

Switching the ionizer on/off

ON = I **OFF =** **0**



When the ionizer is switched on, a red dot will be visible on the switch.

NO FROST APPLIANCES

Control unit 2,3 and 4



Adaptive Intelligent System

(only with control units 3 and 4)
Innovative sensor technology allows adjusting appliance operation to the user's habits or behaviour. Adaptive intelligent system monitors, analyzes, and records on weekly basis the use of appliance and adapts appliance operation to the perceived patterns. If the appliance is able to anticipate increased frequency of door opening, the appliance will automatically lower the temperature before such time to reduce heating of the food as the door is opened more often.

Recommended distribution of food in the appliance

Recommended distribution of food in the appliance

Sections of the refrigerator:

- **upper part**: canned food, bread, wine, pastry etc.
- **middle part**: dairy products, ready-made meals, desserts, soft drinks, beer, cooked food, etc.
- **Fresh/Zero bin**: - meat, meat produce, delicatessen;
- **Fruit and vegetable bin**: fresh fruit, vegetables, salads, root vegetables, potatoes, onions, garlic, tomatoes, tropical fruit, sauerkraut, turnips etc.

Sections in the refrigerator compartment door:

- **upper/middle door bins**: eggs, butter, cheese etc.
- **lower door bins**: beverages, cans, bottles etc.

Freezer sections:

- freezing, storage of frozen food (see Freezing and Storing Frozen Food).



413758

Storing food in the refrigerator

Important warnings regarding food storage

⚠ **Correct use of the appliance, appropriate packaging, maintaining the right temperature, and observing the food hygiene standards has a decisive impact on the quality of food storage.**

⚠ **Observe the expiry dates for the food, specified on the packaging.**

⚠ **Food stored in the refrigerator should be kept in closed containers or appropriate packaging to prevent them from emitting or receiving odours.**

⚠ **Do not store inflammable, volatile, and explosive substances in the refrigerator.**

⚠ **Bottles with high alcohol content should be tightly sealed and stored in an upright position.**

⚠ **Some organic solutions, essential oils in lemon and orange peel, butter acid, etc. may damage the plastic surfaces in case of a prolonged contact, causing damage and premature ageing of these materials.**

⚠ **Unpleasant odour warns of lacking cleanliness of the appliance or perished contents (see Cleaning the Appliance).**

⚠ **If you are leaving home for a longer period of time, remove perishables from the refrigerator.**

Food storage times

Recommended storage time in the refrigerator

Type of food	Time
eggs, marinades, smoked meat	up to 10 days
cheese	up to 10 days
root vegetables	up to 8 days
butter	up to 7 days
deserts, fruit, ready-to-eat food, chunks of raw meat	up to 2 days
fish, raw minced meat, seafood	up to 1 day

Storing food in the FreshZone drawer

In the **FreshZone** compartment, food stays fresh longer than in a conventional refrigerator, retaining more flavour and nutrients. Decay and loss of mass are slowed down; therefore, fruit and vegetables remain fresh and natural longer.
For optimum performance, the drawer should be fully closed.

- When buying food, make sure it is fresh as this will determine the quality of the food, as well as how long it will keep in the fridge.
- Store the food in closed containers or appropriate packaging to prevent them from emitting or receiving odours.
- Take the food from the drawer 30-60 minutes before use to allow the aroma and flavour develop at room temperature.
- Food sensitive to low temperature and not appropriate for storage in the **FreshZone** drawer include the following: pineapple, avocado, bananas, olives, potatoes, eggplant, cucumbers, beans, peppers (capsicum), melons, watermelons, pumpkins, squash, zucchini etc.

- To remove the drawer:
  - Pull out the drawer until it is blocked.
  - Then, lift it at the front and pull it all the way out.



Storing food in the ZeroZone drawer

The **ZeroZone** drawer allows storing a wide range of fresh food up to three times as long as in a conventional refrigerator. Food will remain fresh longer and they will retain the flavour and nutrients. Temperature in the drawer is around 0°C. If the temperature of the environment in which the appliance is installed is lower than 16C, we recommend setting the refrigerator compartment temperature to 4°C or lower. For optimum operation, the drawer must be fully closed.

- When buying food, make sure it is fresh as this will determine the quality of the food, as well as how long it will keep in the fridge.
- Store the food in closed containers or appropriate packaging to prevent them from emitting or receiving odours and humidity.
- Take the food from the drawer 30-60 minutes before use to allow the aroma and flavour develop at room temperature.
- Food sensitive to low temperature and not appropriate for storage in the **FreshZone** drawer include the following: pineapple, avocado, bananas, olives, potatoes, eggplant, cucumbers, beans, peppers (capsicum), melons, watermelons, pumpkins, squash, zucchini etc.
- To extend freshness of food stored in the **ZeroZone** drawer as much as possible, set the refrigerator temperature to 1°C. Actual temperature in the ZeroZone drawer may fall below 0°C; therefore, place the food that is sensitive to freezing to one of the upper sections of the refrigerator or in the fruit and vegetables bin.

- To remove the drawer:
  - Pull out the drawer until it is blocked.
  - Then, lift it at the front and pull it all the way out.



Approximate storage time in the ZeroZone drawer*

Type of food	Time
sausages, cold cuts, beef, pork, venison, raw meat	up to 7 days
Poultry	up to 5 days
fish	up to 4 days
seafood	up to 3 days
Vegetables:	
cabbage, garlic, carrots	up to 180 days
celery, herbs	up to 30 days
Green lettuce, cauliflower, radicchio, rhubarb	up to 21 days
broccoli, asparagus, kale, Chinese cabbage, kohlrabi, radish	up to 14 days
onions, mushrooms, spinach, peas	up to 7 days
Fruit:	
apples	up to 180 days
pears, kiwi	up to 120 days
grapes, quinces	up to 90 days
peaches	up to 30 days
redcurrant, gooseberries, plums	up to 21 days
apricots, blueberries, cherries	up to 14 days
raspberries, strawberries	up to 3-5 days
Other:	
milk	up to 7 days
butter	up to 30 days
cheese	up to 30 days

* depending on the quality and freshness of food

Freezing and storing frozen food

Freezing process

⚠ **Maximum amount of fresh food that may be inserted at once is specified on the appliance rating plate. If the amount of food to be frozen exceeds the indicated amount, the quality of freezing will be inferior; in addition, the quality of the food already frozen will deteriorate.**

- To make use of the entire freezer volume, remove all drawers. Place the food directly on the shelves and on the freezer bottom.
- Activate the super freeze function 24 hours before freezing fresh food:
  - **Control unit 1**: rotate the **A** dial towards **the thickest part of the marking;**

413758

- **Control unit 2**: rotate th**e A** dial to position ✳**.**
- **Control unit 3**: press the **B** key repeatedly until the symbol **D** lights up;
- **Control unit 4**: press the **H** key.

After this time, insert the fresh food into the freezing compartment.

Make sure the fresh food is not in contact with the food that is already frozen!
The most suitable place for freezing a large amount of fresh food is the upper section of the freezer.

- When freezing smaller quantities of food (1-2 kilograms), activating the super freeze function is not required.
- After 24 hours, the food can be moved to other freezer compartments and the freezing process can be repeated as necessary.
- After the freezing process is completed, rotate the **A** dial back to the desired setting (only with control units 1 and 2).

Important warnings on freezing fresh food

⚠ **Only freeze the food that is suitable for freezing in the freezer. Make sure the food you freeze is of high quality and fresh.**

⚠ **Choose appropriate packaging and use the packaging correctly.**

⚠ **Packaging should not be permeable to humidity; it should be airtight to prevent the food from drying out and loss of vitamins.**

⚠ **Label the food; indicate the type of food, amount, and date of freezing.**

⚠ **It is important that the food is frozen as quickly as possible. Therefore, keep the packages small. Refrigerate the food before freezing.**

Storage of industrially frozen food

- When storing and using frozen food, observe the manufacturer's instructions. Temperature and expiry date are indicated on the packaging.
- Only choose food with undamaged packaging, stored in freezers at temperatures of -18°C or lower.
- Do not purchase food covered in frost as this indicates they have been partly defrosted several times and that they are of inferior quality.
- Protect the food from thawing during transport. In case of an increase in temperature, storage time will be shorter and quality will deteriorate.

Frozen food storage time

Recommended storage time in the freezer

Type of food	Time
fruit, beef	from 10 to 12 months
vegetables, veal, poultry	from 8 to 10 months
Venison	from 6 to 8 months
Pork	from 4 to 6 months
minced meat	4 months
bread, pastry, ready-to-eat meals, lean	3 months
entrails	2 months
smoked sausage, fatty fish	1 month

Defrosting frozen food

Freezing the food does not kill the microorganisms. After the food is defrosted or thawed, bacteria is re-activated and the food spoils quickly. Use the partially or completely defrosted food as soon as possible.
Partial thawing decreases the nutritive value of the food, particularly fruit, vegetables, and ready-to-eat food.

Defrosting the appliance

Automatic refrigerator defrosting

Refrigerator does not need defrosting because the ice on the back interior wall is thawed automatically.
Any accumulated ice will melt when the compressor unit is inactive. Drops will flow through an opening in the refrigerator rear wall into a tray fitted above the compressor, from where they will evaporate.

If an excessive layer of ice is formed on the rear wall of refrigerator interior (3-5 mm), switch off the appliance and defrost the appliance manually.

Defrosting a conventional freezer

- Defrost the freezer when an approximately 3-5 milimeter layer of of frost or ice has built up.
- 24 hours before defrosting, activate the super freeze function to additionally cool the food (see section »Freezing Process«).

After this period, remove the food from the freezer and protect them from defrosting.

- Switch off the appliance (see chapter Switching the appliance on/off) and unplug the power cord.
- Do not use any defrosting sprays as they may melt the plastic parts or harm your health.
- Do not use a knife or any other sharp object to remove the frost, because you may damage a pipe of the cooling system.
- To speed up the defrosting process, place a pot of hot water on the glass shelf.
- Clean and dry the appliance interior (see Cleaning the Appliance).
- Before placing the food into the freezer, switch on the appliance and rotate the **A** dial back to the desired setting (only with control units 1 and 2).

Defrosting a NO FROST freezer

- The NO FROST freezer will defrost automatically. Occasional frost that may appear on the walls will disappear automatically.
- Build-up of ice or frost in the freezer compartment can be a result of abnormal use of appliance (door opened too frequently and/or too long, door not properly closed etc.). In this case, unplug the appliance, remove the food from the freezer and protect them from defrosting.
  Clean and dry the freezer interior. Before returning the frozen food into the freezer, switch on the appliance and select the desired setting.

Cleaning the appliance

Before cleaning, unplug the appliance from the power mains – switch off the appliance (see chapter Switching the Appliance On/Off) and unplug the power cord from the wall outlet.

- Use a **soft cloth** to clean all surfaces. Cleaners that contain **abrasive substances, acids, or solvents are not suitable for cleaning** as they may damage the surface.

Clean the appliance **exterior** with water or a mild solution of suds. Lacquer-coated and aluminium surfaces may be cleaned with lukewarm water to which you have added a mild detergent. Use of cleaners with low alcohol content is allowed (e.g. window cleaners).
Do not use cleaners containing alcohol for cleaning plastic materials.

Appliance interior can be cleaned with lukewarm water to which you can add some **vinegar**.

- A gutter and an opening through which the water from thawed ice flows are located underneath the cooling panel that cools the refrigerator interior. The gutter and the opening may not be clogged. Inspect them often and clean if necessary (e.g. with a plastic straw).
- Frost or ice build-up, 3-5 mm thick, will increase power consumption. Therefore, it should be regularly removed (does not apply to NO FROST freezer). Do not use any sharp objects, solvents, or sprays.



- The **condenser** unit mounted on the (exterior) back wall should always be kept clean, free of dust or deposits resulting from kitchen smoke or fumes.. Occasionally clean the dust using a soft non-metal brush or a vacuum cleaner.



- Also clean the **tray** above the refrigerator compressor. If you remove it, replace it after cleaning. Make sure it is placed horizontally.
- After cleaning, switch the appliance back on and insert the food.

Troubleshooting

Problem:	Cause or remedy:
Appliance is connected to the power mains but it does not work.	• Make sure there is voltage in the power outlet and that the appliance is switched on.
Cooling system operates continuously for a long period of time: 	• Too high environment temperature.
	• Door opened too frequently or too long.
	• Door not closed correctly (possible impurities on the seal, misaligned door, damaged seal etc.).
	• Too much fresh food inserted at once.
	• Sensor in the refrigerator (A or B) blocked by fresh food. Make sure the air can circulate around the sensor (only with some models).
	• Insufficient compressor and condenser cooling. Check the air circulation behind the appliance and clean the condenser unit.
Excessive build-up of ice on the back wall of refrigerator interior can be a result of the following:	• Door opened too frequently or too long.
	• Warm food placed in the refrigerator.
	• Food in contact with the back interior wall of the refrigerator.
	• Poor door sealing. If the seal is dirty or damaged, clean it or replace it.
Build-up of ice or frost in the freezer interior may be a result of the following:	• Door opened too frequently or too long.
	• Door not properly closed.
	• Poor door sealing.
	• If the seal is dirty or damaged, clean or replace it.
Condensate (dew) on the shelf above the drawers:	• This is a transient phenomenon which cannot be entirely avoided in periods of high environment temperature and humidity. It subsides when temperature and humidity are normalized. We recommend cleaning the drawers more frequently and wiping the droplets occasionally. • Open the humidity control slider. • Place the food in to bags or other airtight packaging.
Water leaking from the refrigerator:	• Clogged water discharge opening or water dripping past the water gutter.
	• Clean the clogged opening, for example using a plastic straw.
	• If a thick layer of ice builds up, defrost the appliance manually (see Defrosting the Appliance).
The **B** key will flash (applies to control unit 4).	• Door opened too frequently or too long.
	• Door not closed correctly (possible impurities on the seal, misaligned door, damaged seal etc.).
	• A longer power failure.
	• Too much fresh food inserted at once.

Problem:	Cause or remedy:
Door is difficult to open:   	• If you are trying to open the freezer door after just having closed it, this could be difficult to do. As you open the door, some cool air escapes from the appliance and it is replaced by warm air from the environment. When this air is cooled, negative pressure is generated which results in problems as you try to open the door. After a few minutes, the condition is normalized and the door can be easily opened again. • To relieve this effect, use a decompression plate provided in the bag with the instruction manual. Paste the plate onto the front edge of the cabinet, always on the side of the door hinge, as indicated in the figure (only with some models).
LED lighting does not work:	• If LED lighting does not work, call a service technician.
Indication of error code on the display (only with some models):	• If E appears on the display, call a service technician.
Temperature in the freezer too high:  	• Set the manual flap (located behind the fruit and vegetables bin) by pressing the button and moving it to position 1 (only with some models).
Temperature in the refrigerator too high:  	• Set the manual flap (located behind the fruit and vegetables bin) by pressing the button and moving it to position 3 (only with some models).

If none of the instructions above fixes your problem, call the nearest authorized service center and state the type, model, and serial number found on the rating plate/label which is located in the appliance interior.

Information about appliance noise

Cooling in refrigerator freezers is made possible by a cooling system that also includes a compressor (and a fan with some appliances), which generates some noise. The level of noise depends on installation, proper use, and age of the appliance.

- **After connecting the appliance to the power mains**, compressor operation, or the sound of flowing liquid, may be somewhat louder. This is not a sign of malfunction and it will not affect the useful life of the appliance. In time, appliance operation and this noise will become quieter.
- Sometimes, **unusual or loud noise** may appear during appliance operation; these are mostly the result of improper installation:
  - The appliance must stand level and stable on a solid base.
  - The appliance may not be in contact with a wall or adjacent furniture.
  - Make sure the interior equipment sits firmly in its place and that the noise is not caused by cans, bottles or other containers placed next to each other.
- Due to the higher workload on the cooling system when the door is opened more frequently or for a longer time, when a large amount of fresh food is introduced, or when intensive freezing or cooling functions are activated, the appliance can temporarily generate more noise.

WE RESERVE THE RIGHT TO MAKE CHANGES THAT DO NOT AFFECT THE FUNCTIONALITY OF THE APPLIANCE.

HZF3361 E
COMBI FS-600

en (01-14)